

Application Programming Interface (API) at EC-Ship System for System Integration on HKPost Mail Tracking

Version: 0.3

Last Updated: 28 April 2022

Amendment History

Version	Amendment	Description	Author /
	Date		Updated By
0.1	Mar 2017	Draft Version	CW Lai
0.2	July 2017	New status code	CW Lai
0.3	April 2022	Change Production Site URL	Ryan Chan

Version 0.2 Page 1 of 6

Table of Contents

1.	HKPost Mail Tracking Web Services URL	. 3
2.	HKPost Mail Tracking Web Services Authentication	. 3
3.	HKPost Mail Tracking API – Track and Trace mail item delivery status	. 4
4.	Appendix A – Status Code and Error Message	. 6

Version 0.2 Page 2 of 6

1. HKPost Mail Tracking Web Services URL

The Hongkong Post Mail Tracking API service is provided by the EC-Ship API platform, the testing and production URL is shown as follow:

Testing Site URL: https://ec-ship-uat.hongkongpost.hk/HKP_MailTrack_API/services

Production Site URL: https://partner.hongkongpost.hk/HKP_MailTrack_API/services

Note1: Only authorized IP addresses are allowed to access this URL

Note2: Request limit per day: 100,000 (Please contact Hong Kong Post if special arrangement is required)

Note3: The frequency of request: 100ms, system will refuse the request if frequency of request exceed the limit. Please group the tracking item into one request as possible.

Note4: Only the sender of the mail item prepared on EC-Ship platform and MySpeedPost platform is allowed to get the track and trace info. Please associate the EC-Ship/MySpeedPost account with EC-Ship API account on API-portal.

2. HKPost Mail Tracking Web Services Authentication

Authentication key is required to call EC-Ship API. The credential is provided registered EC-Ship API users. Credential must be included in your request SOAP message as specified in EC-Ship API. Without this information, your API request will be rejected.

Parameter	Data Type	Length Constraint	Not Null?	Remark
USERNAME	TEXT	20	Yes	API Username
PASSWORD	TEXT	20	Yes	Credentials for reject unauthorized party to use the API. These credentials must be included in your code as specified in the Web Services technical documentation. Transactions without proper credentials will be rejected.

Version 0.2 Page 3 of 6

3. HKPost Mail Tracking API – Track and Trace mail item delivery status

Partner should call this request to send the item numbers (also known as tracking numbers) to Hongkong Post system. The system will return the mail items' delivery status

getItemDeliveryStatus Request

Parameter	Data Type	Length Constraint (byte)	Mandatory	Remark
integratorUsername	String	20	Y	API username
lang	String	1	Y	Language code A' - English, Traditional Chinese and Simplified Chinese message will be returned 'E' - Only English message will be returned 'C' - Only Traditional Chinese message will be returned 'S' - Only Simplified Chinese message will be returned In case language code "E", "C", "S" is received, values of other languages will be returned as empty value.
An array of Item No (max 30 items)				
itemNo	String	13	Y	Mail item tracking number (E.g. RB000000010HK)

Version 0.2 Page 4 of 6

$get Item Delivery Status\ Response$

Parameter	Data Type	Description	Example
status	Number	Reference to Appendix A	0
errMsg	String	Error message	
itemCount	Number	No. of message returned	30
An array of Delivery Resu	lt (max 30 iter		
itemNo String		Mail item tracking number	RB00000010HK
status	Number	Reference to Appendix A	0
errMsg String		Error message	
postingDateTime	String	The posting date and time of the item in DD-MM-YYYY HH24:MI	27-02-2017 16:00
dropOffPoint_e	String	Drop-off Point in English	Queen's Road Post Office
dropOffPoint_c	String	Drop-off Point in Traditional Chinese	皇后大道郵政局
dropOffPoint_s	String	Drop-off Point in Simplified Chinese	皇后大道邮政局
orgCnty_code	String	Original country code	НК
		Reference to Appendix B	
orgCnty_e	String	Original in English	HONG KONG
orgCnty_c	String	Original in Traditional Chinese	香港
orgCnty_s	String	Original in Simplified Chinese	香港
destCnty_code	String	Destination country code	НК
·		Reference to Appendix B	
destCnty_e	String	Destination in English	HONG KONG
destCnty_c	String	Destination in Traditional Chinese	香港
destCnty_s	String	Destination in Simplified Chinese	香港
milestone_e	String	Milestone description in English	Delivered
milestone_c	String	Milestone description in Traditional Chinese	已成功派遞
milestone_s	String	Milestone description in Simplified Chinese	已成功派递
Event Detail (A list of e	_		
eventDateTime	String	The event date and time (In the time zone of the location) in DD-MM-YYYY HH24:MI	01-03-2017 11:00
eventLocation_code	String	The location country code	HK
eventLocation_e	String	The location of the event in English	HONG KONG
eventLocation_c	String	The location of the event in Traditional Chinese	香港
eventLocation_s	String	The location of the event in Simplified Chinese	香港
eventMsg_e String		The message of the event in English	Delivered
eventMsg_c	String	The message of the event in Traditional Chinese	成功派遞
eventMsg_s	String	The message of the event in Simplified Chinese	成功派递

Version 0.2 Page 5 of 6

4. Appendix A – Status Code and Error Message

Status Code	Meaning
0	Success
1001	item number does not exist
1002	Invalid item number format
1003	Tracking period has been expired
1004	Item no not allowed to enquiry
9991	Exceed API request frequency
9992	Invalid Credential
9993	Invalid API format
9994	Exceed API request limit
9995	Exceed the max. enquiry items
9996	Invalid Language
9997	Empty item number array
9998	Invalid input
9999	Service temporary unavailable

Version 0.2 Page 6 of 6